### (19) World Intellectual Property Organization

International Bureau





# (43) International Publication Date 7 April 2005 (07.04.2005)

#### **PCT**

# (10) International Publication Number $WO\ 2005/031385\ A1$

(51) International Patent Classification7: 7/481, G02B 6/28, G01S 17/89

G01S 7/483,

(21) International Application Number:

PCT/GB2004/004061

(22) International Filing Date:

24 September 2004 (24.09.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0322564.6 03256086.4 26 September 2003 (26.09.2003) GB 26 September 2003 (26.09.2003) EP

(71) Applicant (for all designated States except US): MBDA UK LIMITED [GB/GB]; Six Hills Way, Stevenage, Hertfordshire SG1 2DA (GB).


(72) Inventors; and

(75) Inventors/Applicants (for US only): MILLER, Lee, Douglas [GB/GB]; MBDA Uk Limited, P.O. Box 5. Filton, Bristol, Avon BS34 7QW (GB). JENNINGS, Martyn, Robert [GB/GB]; MBDA Uk Limited, P.O. Box 5, Filton, Bristol, Avon BS34 7QW (GB).

- (74) Agent: BAE SYSTEMS PLC; Intellectual Property Department, Lancaster House, P.O. Box 87, Farnborough Aerospace Centre, Farnborough, Hampshire GU14 6YU (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: OPTICAL IMAGINS SYSTEM WITH OPTICAL DELAY LINES



(57) Abstract: An electromagnetic signal processing system (10) comprises a plurality of optical fibre arrays (11, 12, 13, 14, 15 and 16) each having a cluster of optical fibres with their one ends (40) oriented to receive electromagnetic radiation from free-space, or to transmit electromagnetic radiation into free-space. Received electromagnetic radiation passes through respective array outputs (21, 22, 23, 24, 25 and 26) and optical delays (50, 51; 55, 56; 65) to the input (68) of a signal detector (69). Transmitted electromagnetic radiation from sources (71, 72) passes through optical delays (50, 51; 55, 56) to array inputs (21, 22, 23, 24, 25 and 26) so that the one ends (40) of the optical fibres transmit the electromagnetic radiation into free-space.

## WO 2005/031385 A1



with international search report

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.